



NOTES:

1. ALL MATERIALS, WORKMANSHIP, AND INSTALLATION SHALL BE IN CONFORMANCE WITH THE STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION AS AMENDED BY TOWN OF FRIDAY HARBOR STANDARDS.
2. ALL MATERIALS EXCEPT HMA SHALL BE COMPACTED 95% DENSITY. HMA SHALL BE COMPACTED TO 91%.
3. TOWN REPRESENTATIVE SHALL BE PRESENT DURING COMPACTION EFFORT. APPLICANT SHALL PROVIDE 2 BUSINESS DAYS NOTICE.
4. IF STREET PAVEMENT IS LESS THAN 5 YEARS OLD, THE APPLICANT SHALL GRIND AND INSTALL A 2 INCH OVERLAY. FOR LONGITUDINAL UTILITY INSTALLATIONS THE APPLICANT SHALL GRIND AND INSTALL A 2 INCH OVERLAY FOR HALF A STREET WIDTH. FOR TRANSVERSE CUTS, A 150 FOOT LONG, MINIMUM, GRIND AND OVERLAY SHALL BE INSTALLED.

NO SCALE



APPROVAL

Wayne R. Haufle

PUBLIC WORKS DIRECTOR

**TRENCH PAVEMENT
RESTORATION**

DATE
01/21/2022

DRAWING NO.

U-7

REV: